

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/010289

International filing date: 28 March 2005 (28.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/556,666
Filing date: 26 March 2004 (26.03.2004)

Date of receipt at the International Bureau: 12 May 2005 (12.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1317005

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

May 04, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/556,666

FILING DATE: *March 26, 2004*

RELATED PCT APPLICATION NUMBER: *PCT/US05/10289*



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

PROVISIONAL PATENT APPLICATION
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No: 20044/10018

PROVISIONAL PATENT APPLICATION TRANSMITTAL

Mail Stop Provisional Patent Application
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Transmitted herewith for filing is the provisional patent application under 37 CFR 1.53(c) of

Inventor(s): **Paul C. BURKE, Mark HOLMES, and John A. RUNZEL**

Residences: 470 Heather Lane, Lake Forest, IL 60045; 52 W. Honeysuckle Drive;
Round Lake Beach, IL 60073; and 29W047 Bode Road, Elgin, IL
60120

Title: **"Adjustable Length Cabling Systems"**

1. Application Papers Enclosed

- 1 Title Page
- 6 Pages of Specification
(excluding Claims, Abstract, Sequence Listing & Drawings)
- 7 Sheet(s) of Drawings (Figs. 1 to 7)

☐ Formal
☒ Informal

CERTIFICATION UNDER 37 CFR 1.10

I hereby certify that this Provisional Patent Application Transmittal and the documents referred to as enclosed therewith are being deposited with the United States Postal Service on **March 26, 2004** in an envelope addressed to Mail Stop Provisional Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 utilizing the "Express Mail Post Office to Addressee" service of the United States Postal Service under Mailing Label No. EV 440113911 US.


Raquel Mondon

2. Small Entity Status

- ☒ Applicant claims small entity status. See 37 CFR 1.27.
- ☐ A small entity statement is(are) attached.

3. Additional Papers Enclosed

- ☐ Declaration of Biological Deposit
- ☐ Computer readable copy of sequence listing containing nucleotide and/or amino acid sequence
- ☐ Microfiche computer program
- ☐ Associate power of attorney
- ☐ Verified translation of a non-English patent application
- ☐ An assignment of the invention
- ☒ Return Receipt Postcard
- ☐ Other (e.g. declaration or oath)

4. Filing Fee Calculation (37 CFR 1.16)

- ☒ Provisional Application (\$80.00/\$160.00) Filing Fee: \$80.00
- ☐ Other Fees (e.g. Recording Assignment) Filing Fee:

Total Fees Enclosed: **\$80.00**

5. Method of Payment of Fees

- ☒ Enclosed is our firm check in the amount of: \$80.00
- ☐ Charge Deposit Account No. 50-2455 in the amount of: \$
A copy of this Transmittal is enclosed.

6. Deposit Account and Refund Authorization

The Commissioner is hereby authorized to charge any deficiency in the amount enclosed or any additional fees which may be required during the pendency of this application under 37 CFR 1.16 or 37 CFR 1.17 or under other applicable rules (except payment of issue fees), to Deposit Account No. 50-2455. A copy of this Transmittal is enclosed.


Please refund any overpayment to Grossman & Flight, LLC at the address below.

7. Correspondence Address

Respectfully submitted,

GROSSMAN & FLIGHT, LLC
20 North Wacker Drive
Suite 4220
Chicago, Illinois 60606
(312) 580-1020


By:


Mark G. Hanley
Registration No.: 44,736

March 26, 2004

Joint Inventors
20044/10018

"EXPRESS MAIL" mailing label No. EV 440113911 US.
Date of Deposit: March 26, 2004
I hereby certify that this paper (or fee) is being deposited
with the United States Postal Service "EXPRESS MAIL
POST OFFICE TO ADDRESSEE" service under 37 CFR
§1.10 on the date indicated above and is addressed to: Mail
Stop Provisional Patent Application, Commissioner for
Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450


Raquel Mondon

PROVISIONAL APPLICATION FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

Be it known that We, **Paul C. Burke**, a citizen of the United States, residing at 470 Heachter Lane, Lake Forest, Illinois 60045; **Mark Holmes**, a citizen of the United States, residing at 52 W. Honeysuckle Drive, Round Lake Beach, Illinois 60073; and **John A. Runzel**, a citizen of the United States, residing at 29W047 Bode Road, Elgin, Illinois 60120 have invented a new and useful **ADJUSTABLE LENGTH CABLING SYSTEMS**, of which the following is a specification. My legal representative for this provisional patent application is Mark G. Hanley (Reg. No. 44,736) of Grossman & Flight, 20 N. Wacker Drive Suite 4220, Chicago, IL 60606; phone 312.580.1020.

ADJUSTABLE LENGTH CABLING SYSTEMS

FIELD OF THE DISCLOSURE

[0001] The present disclosure relates generally to cabling and, more particularly, to adjustable length cable systems.

BACKGROUND

[0002] Seating arrangements associated with transportation such as, for example, busses, trains, aircraft, etc. typically provide multiple rows of seats for passengers. Each row may include one or more adjacent seats, which may be joined via a mounting rail assembly, base unit, or any other suitable frame or structure that facilitates attachment of the seats to the transport. In addition, the rows of seats are typically arranged to provide a walkway or aisle, which is often located along the longitudinal axis of the transport. Thus, rows of seats may be disposed on each side and along the length of such an aisle or walkway.

[0003] In the case of modern commercial aircraft, passenger seats typically provide a variety of electronic functions that require power signals, communication signals, etc. In particular, as is well known, aircraft passenger seats typically provide access to in-flight entertainment such as audio programming, video programming, etc., communication systems such as, for example, telephone service, etc. To convey the electrical signals needed to all of the passenger seats, fixed length cables or wiring harnesses electrically couple one row of seats to a next row of seats. In this manner, rows of passenger seats may be daisy-chained together with these fixed length cables or wiring harnesses to provide electrical power signals, communication signals, etc. to all of the seats.

[0004] In some transports, particularly in commercial aircraft, it is often desirable to change the distance between the rows of seats to configure the aircraft for a different flight routing or purpose. Unfortunately, because the rows of seats are often electrically coupled to each other using fixed length cables, a change (e.g., an increase) in seat row spacing typically requires replacement of the existing fixed length cables with fixed length cables having an appropriate length. Of course, changing seat-to-seat cabling is a time consuming and expensive process. In addition, many aircraft manufacturers and commercial airline companies do not maintain a sufficient or complete stock (or in some cases any stock) of different length cable assemblies. As a result, the relatively long lead times associated with cable assemblies make a relatively quick change in seat spacing impractical.

[0005] The use of fixed length seat-to-seat cabling is further complicated by the fact that spacing between seat rows is typically not consistent for all rows along the length of the aircraft. Specifically, the large numbers and variety of electrical and mechanical sub-systems that are distributed throughout an aircraft often require a particular row of seats to be located slightly closer or slightly further from another row of seats to prevent, for example, mechanical interference between one or more seats and one or more of these sub-systems.

[0006] Additionally, the above-mentioned fixed length cable assemblies used in connection with aircraft must comply with stringent temperature and other environmental requirements. Unfortunately, known cables compliant with these requirements typically utilize a relatively large amount of insulation for each of a plurality of the multiple conductors making up the cable as well as a relatively thick (and stiff) outer jacket. Such large amounts of insulation result in a relatively high

stiffness and weight per unit length, which are undesirable characteristics, particularly for seat-to-seat cabling applications in commercial aircraft.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Fig. 1 depicts a row of aircraft seats.

[0008] Fig. 2 depicts a known manner in which fixed length cable assemblies are used to provide power, data and other signals to aircraft seats and to electrically couple one row of seats to another.

[0009] Fig. 3 depicts an example adjustable length cable system.

[0010] Fig. 4 depicts another example adjustable length cable system.

[0011] Fig. 5 depicts an example manner in which the adjustable length cable systems of Figs. 3 and 4 may be used to couple signals between aircraft seats.

[0012] Fig. 6 is a detailed depiction of one manner in which the cabling used in the examples of Figs. 3 and 4 may be implemented.

[0013] Fig. 7 is a detailed depiction of one manner in which the Ethernet cable shown in Fig. 6 may be implemented.

DETAILED DESCRIPTION

[0014] Fig. 1 depicts a row of aircraft seats. While the row of seats depicted in Fig. 1 shows three adjacent seats, any other number of seats could be used instead. Further, it should be understood that while the example adjustable cable systems described herein are described as being used in connection with aircraft seats, the example adjustable cables systems are more generally applicable. For example, the adjustable cable systems described herein may be used in connection with any other types of seats. Still further, the adjustable cable systems described herein may be used in any other applications desired.

[0015] Fig. 2 depicts a known manner in which fixed length cable assemblies are used to provide power, data and other signals to aircraft seats and to electrically couple one row of seats to another. As shown in Fig. 2, cables having extra length are used to enable the rows of seats to be moved apart without having to replace the cable assemblies. However, as depicted in Fig. 2, the extra length of cabling is loosely placed underneath the seat and, as a result, presents a potential hazard and/or failure if the excess cabling is dislodged and falls onto the floor underneath the seat.

[0016] Fig. 3 depicts an example adjustable length cable system. The example system depicted in Fig. 3 includes a cable storage unit 300 and a cable assembly 302 having connectors or terminations 304, 306, 308 and 310. The cable storage unit 300 includes a spool or reel 312 upon which a portion of the length of the cable assembly 302 is wound. The cable storage unit 300 also includes a base or housing 314. The housing 314 includes a plurality of circumferentially spaced tabs 316 configured to enable the reel 312 to be rotatable relative to the housing 314. Additionally, the tabs 316 may be further configured to retain the wound portion of the cable assembly 302 against the reel 312. The housing 314 may also provide mounting holes 318 to facilitate mounting of the cable storage unit 300 underneath a seat, or in some other location. The connectors 304, 306, 308 and 310 may include any desired combination of DIN connectors, RCA connectors, or any other types of electrical connectors.

[0017] In operation, the effective length of the adjustable cabling system shown in Fig. 3 may be changed by rotating the reel 312 relative to the housing 314. In the example of Fig. 3, rotating the reel 312 clockwise reduces the effective (e.g., overall) length of the cabling system and rotating the reel 312 counter-clockwise increases the effective length of the cabling system.

[0018] Fig. 4 depicts another example adjustable length cable system. Similar to the example adjustable cabling system depicted in Fig. 3, the example adjustable cabling system of Fig. 4 includes a cable storage unit 400 and a cable assembly 402 having connectors or terminations 404, 406, 408 and 410. In contrast to the example system of Fig. 3, the cable storage unit 400 depicted in Fig. 4 does not include a reel or spool to enable rotatable retraction and/or extension of a length of the cable assembly. Instead, the storage unit 400 provides an internal chamber into which additional length of the cable assembly 402 may be disposed (e.g., by manually pushing a length of the cable assembly 402 into the chamber) and/or extracted (e.g., again by manually pulling a length of the cable assembly 402 from the chamber).

[0019] Fig. 5 depicts an example manner in which the adjustable length cable systems of Figs. 3 and 4 may be used to couple signals between aircraft seats. As shown in the example implementation of Fig. 5, the adjustable length cable systems described herein may be used to eliminate loose lengths of cable (e.g., as depicted in Fig. 2) that facilitate changes in the distances between rows of seats (e.g., in aircraft). As can be seen in the example of Fig. 5, in contrast to known fixed length cable assemblies, the adjustable length cabling systems described herein enable a single type of cabling system to be used to electrically couple power, data and other signals to multiple rows of seats within, for example, aircraft and/or other transports. Further, with the example adjustable length cabling systems described herein, changes in distances between seats can be carried out without having to engage in the costly process of designing, obtaining and installing different fixed length cables.

[0020] Fig. 6 is a detailed depiction of one manner in which the cabling used in the examples of Figs. 3 and 4 may be implemented. As depicted in the example implementation of Fig. 6, the cabling may be a multi-conductor cable configured to

convey various power, data (e.g., Ethernet), and other electrical signals in conformance with commercial aircraft requirements. To reduce weight, and in contrast to prior aircraft cabin cabling, the example cabling of Fig. 6 utilizes Litz wire, which meets the voltage, temperature and flammability requirements (e.g., FAA FAR 25.869) of commercial aircraft. However, other specifications may be met as well. In addition, the outer jacket surrounding the multi-conductor cable depicted in Fig. 6 may be a high temperature braided fabric that provides a high degree of mechanical flexibility, is lightweight, and meets the stringent environmental requirements of commercial aircraft.

[0021] Fig. 7 is a detailed depiction of one manner in which the Ethernet cable shown in Fig. 7 may be implemented. As depicted in Fig. 7, the example Ethernet cable is fabricated using Litz wire to minimize weight, maximize mechanical flexibility while meeting the environmental requirements associated with commercial aircraft. Using the example cabling construction depicted in Figs. 6 and 7, a seventy-five inch long cable may weigh approximately .73 pounds. In contrast, known fixed length cables for use in commercial aircraft seat-to-seat cabling having a length of about 47 inches may weigh more than .85 pounds.

[0022] Although certain methods and apparatus have been described herein, the scope of coverage of this patent is not limited thereto.




FIG. 1






FIG. 2









FIG. 5



Conductors

1 @ 24 awg 19/36; litz wire; white

5 @ 16 awg 19/29; litz wire
colors: black, red, yellow, blue, green

1 @ 26 awg, 100-ohm ethernet cable

Cabling: Planetary, round as possible

Shield: N/A

Performance


Voltage rating - 600 vac

Temperature - 200C

Flammability - shall pass FAA FAR 25.869

FIG. 6

26 awg, 100-phm Ethernet Cable



Conductor

AWG 26; 19x38: litz wire
 Resistance: 42.8 ohms/1000 ft
 4 conductors/4 colors wrapped around (opt) filler
 red, blue, yellow, green

Double Shielded:

Material: 38 awg tinned copper
 Inner shield min 90% coverage
 Outer shield min 85% coverage

Binder:

Use PTFE binder between conductors and shield
 and outside of shield.

Cable Characteristics (desired)

Differential Impedance: 100 +/- 10 ohms
 Capacitance (nom): 13 pF/ft
 Velocity of Propagation (nom): 80 %
 Attenuation (max): 3.2 dB/100m @ 1MHz (1.0 dB/100ft)
 10.5 dB/100m @ 10 MHz (3.2 dB/100 ft)
 36.0 dB/100m @ 100 MHz (11.0 dB/100ft)

Near End Cross Talk

$1 \leq f \leq 100 \text{ MHz}$: NEXT(f) $\geq 64 - 15 \log_{10}(f/0.772)$ (dB)

Structural Return Loss

$1 \leq f \leq 20 \text{ MHz}$: 23 dB
 $20 < f \leq 100 \text{ MHz}$: SLR(f) $\geq \text{SRL}_{20} - 10 \log_{10}(f/20)$ (dB)

Flammability - shall pass FAA FAR 25.869

Temperature - 200C

Voltage Rating - 600 VAC